

Locking Wall Mount Cabinets with Swing Mount

24 Inch Deep Cabinets with Attached Swing Mount – Ships Fully Assembled

Specifications:

Airflow – Front to Rear

Mounting Width – 19"

Rack Space – 15U (26.25")

Overall Height – 30.25"

Overall Depth – 24"

Overall Width – 24"

Rail Style – Square punched utilizing cage nuts

Swing Mount - Cabinet mounted to swing mount to allow rear access when flush mounted to a wall

Shipping Weight and Dimensions -
27"D x 26"W x 33"H
68 lbs

Common Features:

- 19" standard rack mount
- 13" standard rail depth
18" maximum rail depth
- 132 lb static loading max
- Front locking glass door opens to 245 degrees
- Keys and locks for front door and side panels
- Cable entry at top cover and bottom panel
- Two fan locations on top, 4" x 4"
- Optional dual fan unit
- 1.2mm cold rolled steel
- Welded frame
- Includes 10 pcs 12-24 Cage Nuts and screws, ground nuts and washers, hex tool

Compliance:

ANSI/EIA RS-310
IEC297
DINA4149 Part 7
ESTI Standard



Accessories:



WME-FAN

Dual Fan Kit for
27U/42U Cabinets



FME-FANS


Dual 4" Fan Assembly
120VAC

WME-SHELF 10

10" 1U Vented Shelf

WME-SHELF 12

12" 1U Vented Shelf



1U-RACK FAN-TEMP

4 Unit Fan Assembly with
temp display and alert
110VAC



1U-RACK FAN

Same as above without temp display and alert



FME-DRAWER

Locking Sliding Keyboard
Drawer for 4-Post Cabinet